Attomey Docket Number: 1111 008 301 0252

LISTING OF CLAIMS:

- 1. (Currently Amended) A device for disinfecting operatory unit water and lines. comprising:
 - a liquid source such as a pressurized water line or a reservoir:
- an ozone generator using a corona discharge to produce an ozone containing gas;
- a protection system that prevents liquid from the liquid source from entering the ozone generator:
- an ozone mixing system that mixes and dissolves the ozone containing gas in the liquid:
- a circulation system that continuously re-circulates the liquid containing dissolved ozone through a pressurized liquid circulation passageway connected to provide liquid containing dissolved ozone to the operatory unit, said circulation system including a pressure regulator to maintain positive pressure in the circulation passageway:
- a separation system that separates undissolved gas from the ozonated liquid prior to circulating the ozonated liquid through the circulation passageway
- a reducing system that prevents ozone in the separated gas from escaping into the atmosphere during operation of the device by passing the gas through an ozone reducing material before venting to atmosphere; and
- a liquid admitting system that inputs liquid from the liquid source into the mixing system to replace liquid output to the operatory unit; and
- a control system for controlling the device to operate as desired to produce liquid containing dissolved ozone and to circulate and output liquid containing dissolved ozone, said control system further including an ozone sensor, located in said liquid circulation passageway, the ozone sensor connected to said control system and said control system further connected to an alarm to indicate whether the device is operating properly.

Attomey Docket Number: 1111 008 301 0252

(Previously Presented) The device of claim 1 wherein said pressure regulator is selected from the group consisting of: a pressure regulator, a pressure relief valve, and a flow controller

 (Original) The device of claim 1 wherein there is at least one connection in the pressurized liquid circulation passageway for outputting liquid with dissolved ozone.

4. (Canceled)

(Currently Amended) The device of claim 1 wherein said ozone generator is of a size <u>capacity</u> sufficient to generate more ozone than can be dissolved in the liquid flow

6. (Canceled)

- (Original) The device of claim 1 wherein the ozone containing gas is mixed with the liquid by use of a positive pressure pump.
- 8. (Original) The device of claim 1 wherein the ozone containing gas is further mixed with the liquid by use of a static mixer.
- (Original) The device of claim 1 wherein the ozone containing gas is mixed with the liquid by use of a gas diffuser.
- 10. (Original) The device of claim 1 wherein undissolved ozone containing gas is separated from the liquid by use of a porous hydrophobic material
- 11. (Original) The device of claim 1 wherein undissolved ozone containing gas is separated from the ozonated liquid at near atmospheric pressure.

Attomey Docket Number: 1111 008 301 0252

12. (Previously Presented) The device of claim 1 wherein a barrier prevents liquid from entering the ozone reducing material.

13. (Previously Presented) The device of claim 12 wherein liquid is prevented from entering the ozone reducing material by use of a porous hydrophobic barrier.

14. (Original) The device of claim 1 wherein the source of the liquid provides

pressure to circulate and output the ozonated liquid.

15. (Original) The device of claim 1 wherein a pump provides pressure to

circulate and output the ozonated liquid.

16. (Previously Presented) The device of claim 1 further including a waste line, wherein said circulation system circulates the ozonated liquid through the pressurized liquid circulation passageway and liquid that is not output for use from said pressurized liquid circulation passageway is directed to the waste line.

17. (Previously Presented) The device of claim 16 further including a cuspidor draining into the waste line, wherein the ozonated liquid that is directed to a waste line is directed to rinse the cuspidor before entering the waste line.

18. (Original) The device of claim 1 wherein a pump for withdrawing liquid containing dissolved ozone from the ozone mixing system recirculates the liquid under pressure through a loop that conducts the liquid back to the ozone mixing system.

19. (Canceled)

20. (Currently Amended) The device of claim 49 <u>1</u> wherein the ozone generator and ozone mixing system are responsive to the ozone sensor.

Attomey Docket Number: 1111 008 301 0252

21. (Original) The device of claim 1 wherein a valve controls the rate of output flow of the ozonated liquid.

22. (Original) The device of claim 1 wherein a porous hydrophobic barrier is used to prevent liquid from entering the ozone generator.

23. (Previously Presented) The device of claim 1 wherein the ozone generator uses oxygen to produce an ozone containing gas and where the source of oxygen for the ozone generator is dried air supplied to the operatory unit.

24. (Original) The device of claim 1 wherein air is dried by a desiccant protected from moist air by valves when the device is not being operated.

25. (Currently Amended) The device of claim 1 further including a wherein said control system is also responsive to a lack of supply water, for controlling at least the ozone generator and circulation system.

26. (Original) The device of claim 1 wherein a filter is installed in the liquid passageway.

27. (Previously Presented) The device of claim 1 wherein liquid containing dissolved ozone is recirculated through a valved dispensing means.

28. (Previously Presented) The device of claim 27 wherein the valved dispensing means is located as near as possible to the point of use and is responsive to air pressure.

29. (Original) The device of claim 28 wherein the source of the air pressure is air used to drive a turbine in a hand piece.

Attomey Docket Number: 1111 008 301 0252

30. (Currently Amended) A device for disinfecting operatory unit water and lines, comprising:

a liquid source such as a pressurized water line or a reservoir;

an ozone generator using a corona discharge to produce an ozone containing gas;

a protection system that prevents liquid from the liquid source from entering the ozone generator;

an ozone mixing system that mixes and dissolves the ozone containing gas in the liquid:

a <u>re-</u>circulation system_that circulates the liquid containing dissolved ozone through a pressurized liquid circulation loop connected to the operatory unit;

a separation system that separates undissolved gas from the ozonated liquid prior to circulating the ozonated liquid through the circulation passageway \vdots

a reducing system that prevents ozone in the separated gas from escaping into the atmosphere by passing the gas through an ozone reducing material before venting;

a liquid admitting system that inputs liquid from the liquid source into the mixing system to replace liquid output to the operatory unit; and

a control system, controlling operation of the device and a sensor in communication with the control system, wherein liquid level in the a treatment chamber is monitored by the sensor.

- 31. (Currently Amended) The device of claim 1 further-including-a-control system wherein the control system, in response to a period of non-use, turns the device off.
- 32. (Currently Amended) A device <u>method</u> for disinfecting water and lines for medical use, comprising:

a liquid source such as a pressurized water line or a reservoir:

an generating ozone generator using a corona discharge to produce an ozone containing gas;

Attomey Docket Number: 1111 008 301 0252

a-protection-system that prevents <u>preventing</u> liquid from the <u>a</u> liquid source from entering the ozone generator;

an ozone mixing system that mixes and dissolves mixing and dissolving the ozone containing gas in the liquid using an ozone mixing system employing a pump:

- a circulation system that recirculates concurrently recirculating the liquid containing dissolved ozone through a pressurized liquid circulation passageway that includes a return loop connected to said mixing system to conduct unused liquid to said ozone mixing system to provide a regulated supply of liquid containing dissolved ozone for medical use, said ozone mixing system thereby treating the unused liquid as well as any liquid from the liquid source;
- a separation system that separates separating undissolved gas from the ozonated liquid prior to circulating the ozonated liquid through the circulation passageway; and
- a reducing system that prevents ozone in the separated gas from escaping into the atmosphere by passing the gas through an ozone reducing material before venting to atmosphere; and-
- a liquid admitting system that inputs liquid from the liquid source into the mixing system to replace liquid output for the medical use.
- 33. (New) The device of claim 1 further including an ozone sensor in said liquid circulation passageway, located in the return loop after the operatory unit, the ozone sensor connected to said control system and an alarm to indicate whether the device is operating properly.
- 34. (New) The device of claim 33 wherein the ozone generator and ozone mixing system are responsive to the ozone sensor in the circulation system.